


WIND PRESSURE SCHEDULE															
			PRODUCT APPROVAL #	MANUF.	PRODUCT APPROVAL		DESIGN	TESTED SIZE (W x H)	ROUGH OPENING (W x H)	SHUTTER	EMERGENCY ESCAPE	GLASS THICKNESS/ TYPE	EXP. DATE	QTY.	COMMENTS
	ID	MODEL #			P.S.F. +	P.S.F. -									
WINDOW SCHEDULE	A	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+150.0	-150.0	REFER TO STRUCTURAL PLANS	3'-6" x 10'-0"	REFER TO WINDOWS SHOP DRAWINGS FOR ROUGH OPENING.	N	N	LAM. GLASS TYPE A	07/25/2023	1	
	B	SERIES ES-P252 THERMALLY BROKEN OUTSWING ALUMINUM CASEMENT WINDOW	20-1118.04	E.S. WINDOWS	+95.0	-105.0		3'-0" x 6'-6"		N	Y	LAM. GLASS TYPE A	08/25/2026 01/16/2025	1	PROVIDE HZTAL. MULLION BETWEEN CASEMENT-FIXED WINDOW.
	C	SERIES ES-P252 THERMALLY BROKEN OUTSWING ALUMINUM CASEMENT WINDOW	20-1118.04	E.S. WINDOWS	+95.0	-105.0		3'-0" x 5'-0"		N	Y	LAM. GLASS TYPE A	08/25/2026	4	C: SILL HEIGHT: 3'-0"; (3) C1: SILL HEIGHT: 5'-0" (1)
	D	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+106.6	-106.6		12'-0" x 2'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	SILL HEIGHT: 3'-2"
	E	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+125.0	-125.0		3'-0" x 10'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	2	
	F	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+125.0	-140.0		11'-6" x 10'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	G	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+125.0	-140.0		12'-0" x 10'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	H	SERIES ES-P252 THERMALLY BROKEN OUTSWING ALUMINUM CASEMENT WINDOW	20-1118.04	E.S. WINDOWS	+95.0	-105.0		4'-0" x 5'-0"		N	Y	LAM. GLASS TYPE A	08/25/2026 01/16/2025	1	PROVIDE HZTAL. MULLION BETWEEN CASEMENT-FIXED WINDOW.
	I	SERIES ES-P252 THERMALLY BROKEN ALUMINUM FIXED WINDOW	20-1116.02					4'-0" x 3'-0"							
	J	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+106.6	-106.6		12'-0" x 2'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	SILL HEIGHT: 6'-0"
	K	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+125.0	-125.0		3'-6" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	L	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+125.0	-125.0		33'-10" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	M	SERIES ES-P252 THERMALLY BROKEN OUTSWING ALUMINUM CASEMENT WINDOW	20-1118.04	E.S. WINDOWS	+95.0	-105.0		3'-0" x 5'-0"		N	Y	LAM. GLASS TYPE A	08/25/2026 01/16/2025	1	PROVIDE VERTICAL MULLION BETWEEN CASEMENT-FIXED WINDOW, SILL HEIGHT: 3'-0"
	N	SERIES ES-P252 THERMALLY BROKEN ALUMINUM FIXED WINDOW	20-1116.02					5'-0" x 5'-0"							
	O	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+101.7	-101.7		9'-4" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	2	
	P	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+101.7	-101.7		28'-8" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	Q	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+101.7	-101.7		11'-6" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
	Q	SERIES 7000 ALUMINUM WINDOW WALL SYSTEM	21-0212.02	E.S. WINDOWS	+101.7	-101.7		3'-0" x 8'-0"		N	N	LAM. GLASS TYPE A	07/25/2023	1	
EXTERIOR DOORS	D-1	SERIES 9000 ALUMINUM OUTSWING FRENCH DOOR WITH TRANSOM	18-0319.09	E.S. WINDOWS	+80.0	-80.0	REFER TO STRUCTURAL PLANS	6'-0" x 10'-0"	REFER TO WINDOWS SHOP DRAWINGS FOR ROUGH OPENING.	N	Y	LAM. GLASS TYPE A	12/24/2023	1	LEAF HEIGHT: 8'-0"; TRANSOM HEIGHT: 2'-0".
	D-2	SERIES 9000 ALUMINUM OUTSWING FRENCH DOOR WITH TRANSOM	18-0319.09	E.S. WINDOWS	+80.0	-80.0		3'-0" x 10'-0"		N	Y	LAM. GLASS TYPE A	12/24/2023	2	LEAF HEIGHT: 8'-0"; TRANSOM HEIGHT: 2'-0".
	D-3	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+60.0	-60.0		28'-0" x 10'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	2	(4) TRACKS. NON-POCKETED DOORS CONFIGURATION: XXXX-XXXX
	D-4	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+59.1	-59.1		9'-4" x 10'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	2	(3) TRACKS. NON-POCKETED DOORS CONFIGURATION: 0XX
	D-5	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+59.1	-59.1		8'-0" x 10'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	2	(2) TRACKS. NON-POCKETED DOORS CONFIGURATION: 0X
	D-6	MODEL MRD-65 STEEL ROLLING DOOR	20-0417.04	MIAMI ROLLING DOORS	+65.0	-65.0		18'-0" x 10'-0"		N	N	-	12/30/2025	1	
	D-7	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+59.1	-59.1		12'-0" x 8'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	1	(3) TRACKS. NON-POCKETED DOORS CONFIGURATION: XXX
	D-19	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+59.1	-59.1		6'-0" x 10'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	1	(2) TRACKS. NON-POCKETED DOORS CONFIGURATION: 0X
	D-19	SERIES EL400-10 ALUMINUM SLIDING GLASS DOOR	22-0118.05	E.S. WINDOWS	+59.1	-59.1		6'-0" x 10'-0"		N	Y	LAM. GLASS TYPE A	07/20/2027	1	(2) TRACKS. NON-POCKETED DOORS CONFIGURATION: 0X

- NOTE:
- WINDOWS AND DOORS TO BE INSTALLED AS RECOMMENDED BY MANUFACTURERS PRODUCTS APPROVAL.
 - REFER TO ENERGY CALCULATION FOR SHGC AND U-FACTOR FOR GLAZING. (U-0.49 & SHGC=0.23)
 - PROVIDE STEEL REINFORCEMENT MULLION NOA No. 20-1118.13 (09/16/2024).
 - WHEN FRAME IS NOT IDENTIFIED IN PLANS, SEE DOOR ELEVATIONS FOR FRAME SLIDING, OR OUTSWING DOORS.
 - ALL DOORS SHALL BE FLUSH & 1 3/4" THICK U.O.N. AND AS SELECTED BY OWNER.
 - ALL UNIT ENTRY DOORS AND JAMBS TO BE STC: 45.
 - DOOR HARDWARE TO BE SELECTED BY OWNER.
 - CONTRACTOR SHALL SUBMIT DOOR AND HARDWARE SPECIFICATIONS AND SHOP DRAWINGS TO ARCHITECT FOR APPROVAL PRIOR TO PURCHASING ANY COMPONENTS. ALL ACCESSIBLE DOORS TO CONTAIN LEVERS. APPROVED EQUAL IS ACCEPTABLE. SUBMIT SUBSTITUTIONS FOR APPROVAL BY ARCHITECT.
 - CONTRACTOR SHALL COORDINATE WIND PRESSURE DESIGN LOADS WITH N.O.A. WIND PRESSURE LOADS.
 - ALL FRAMES TO BE PAINTED WITH COLOR: T.B.D.
 - SLAB DEPRESSION: GENERAL CONTRACTOR TO COORDINATE DEPTH OF DEPRESSION U=IN SLAB WITH DOOR MANUFACTURER FOR SLIDING GLASS DOOR SYSTEMS AND DOORS.
 - INTERIOR FINISH TO BE FLUSH WITH DOOR SYSTEM SILL (TYP.)
 - WINDOWS PERMIT ON PROJECT UNDER SEPARATE PERMIT FOR CAT. II SAFETY GLASS. ANY CHANGES TO PROPOSED/SPECIFIED WINDOWS SHALL BE SUBMITTED TO ARCHITECT FOR APPROVAL PRIOR TO PURCHASING. SUBSTITUTIONS SHALL BE OF EQUAL CHARACTERISTICS/QUALITY AS SPECIFIED WINDOWS.


(MANUFACTURER OF DOOR, OPERABLE WINDOWS AND MISCELLANEOUS METALS TO PROVIDE SHOP DRAWINGS AND CALCULATIONS AS REQUIRED BY CODE)

DOOR SCHEDULE													
	DOOR								FRAME		GLASS		REMARKS
	ID	LOCATION	W	H	T	MAT.	DESCRIPTION	QTY.	TYP.	FIRE RATING	MAT.	HARDWARE GROUP	
INTERIOR	D-8	GARAGE / MULTIPURPOSE ROOM	3'-0"	8'-0"	1 3⁄4"	WD.	SWING DOOR	2	A	N/A	WD.		
	D-9	POOL BATH / CLOSET BEDROOM 3	2'-4"	8'-0"	1 3⁄4"	WD.	SWING DOOR	2	A	N/A	WD.		
	D-10	POOL BATH / MASTER BEDROOM	3'-0"	8'-0"	1 3⁄4"	WD.	POCKET DOOR	3	B	N/A	WD.		
	D-11	VARIES ROOMS	2'-10"	8'-0"	1 3⁄4"	WD.	SWING DOOR	11	A	N/A	WD.		
	D-12	STAFF ROOM	4'-0"	8'-0"	1 3⁄4"	WD.	DOUBLE BI-FOLD DOOR	1	D	N/A	WD.		
	D-13	AHU	4'-0"	8'-0"	1 3⁄4"	WD.	DOUBLE BI-FOLD DOOR	2	D	N/A	WD.		LOUVERED
	D-14	GUEST CLOSET	6'-0"	8'-0"	1 3⁄4"	WD.	DOUBLE BI-FOLD DOOR	1	D	N/A	WD.		
	D-15	A.H.U. 5 & 6	2'-0"	8'-0"	1 3⁄4"	WD.	BI-FOLD DOOR	2	C	N/A	WD.		LOUVERED
	D-16	BEDROOMS	3'-0"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	5	A	N/A	WD.		
	D-17	BEDROOM 2	8'-0"	8'-0"	1 3⁄4"	WD.	DOUBLE BI-FOLD DOOR	1	D	N/A	WD.		
	D-18	BEDROOM 1 & 3	5'-10"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	4	D	N/A	WD.		
	D-18	BEDROOM 1 & 3	5'-10"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	4	D	N/A	WD.		
	D-18	BEDROOM 1 & 3	5'-10"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	4	D	N/A	WD.		
	D-18	BEDROOM 1 & 3	5'-10"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	4	D	N/A	WD.		
	D-18	BEDROOM 1 & 3	5'-10"	8'-0"	1 3⁄4"	WD.	DOUBLE SWING DOOR	4	D	N/A	WD.		


- NOTES:
- WINDOWS AND DOORS TO BE INSTALLED AS RECOMMENDED BY MANUFACTURERS PRODUCTS APPROVAL.
 - ALL GLAZING SHALL BE TESTED IN ACCORDANCE WITH CPSC 16 CFR PART 1201, AND SHALL BE CAT II SAFETY GLAZING.
 - ROUGH OPENINGS MUST COMPLY WITH MANUFACTURES SPECIFICATIONS.
 - GLAZING IN BATH & SHOWER ENCLOSURE SHALL BE GLAZING CAT. II AS PER B2406.2
 - GLAZING IN SLIDING & SWINGING DOORS SHALL BE SAFETY GLASS CAT. II IF LESS THAN 9 S.F. OR CAT. II IF GREATER THAN 9 S.F. AS TABLE B2406.2(1)
 - GLAZING ADJACENT TO & WITHIN 24" OF A DOOR SHALL BE SAFETY GLAZING CAT.II AS PER B2406.4.2
 - GLAZING WITHIN 60" OF FLOOR LEVEL IN WALLS SURROUNDING TUB OR SHOWER & WITHIN 60" HORIZONTALLY OF TUB OR SHOWER SHALL BE SAFETY GLAZING CAT. II AS PER B2406.4.5.1 & R308.4.5
 - GLAZING IN WINDOWS WHERE THE BOTTOM EDGE OF THE GLAZING IS LESS THAN 18" OR THE TOP EDGE OF THE GLAZING IS GREATER THAN 36" ABOVE THE FLOOR SHALL BE SAFETY GLAZING CAT. II AS PER R308.4.3.
 - SUBMIT SHOP DRAWINGS FOR WINDOWS, DOORS AND HARDWARE TO ARCHITECT FOR APPROVAL PRIOR TO PLACING MANUFACTURING.
 - ALL METAL FRAMES (JAMBS) SHALL BE GROUTED PRIOR TO INSTALLATION. NO KNOCK-DOWN FRAMES SHALL BE INSTALLED.
 - ALL METAL DOORS SHALL HAVE EDGE SEAM (NO CENTER SEAMS).
 - ALL DOORS SHALL HAVE SILENCERS (IVES SR64) INSERTED INTO DOOR JAMBS.
 - CONTRACTOR SHALL CONFIRM ALL ROUGH OPENINGS WITH SELECTED WINDOW / DOOR MANUFACTURERS PRIOR TO CONSTRUCTION OF THE BEAMS / LINTELS (R.O. MAY VARY BY MANUFACTURES). SUBMIT SHOP DRAWINGS FOR WINDOWS, DOORS AND HARDWARE TO ARCHITECT FOR APPROVAL PRIOR TO PLACING MANUFACTURING.




TYPE A



TYPE B



TYPE C



TYPE D

INTERIOR FINISHES

- MEANS OF EGRESS CLASS B
- INDIVIDUAL ROOMS OR LIVING SPACE CLASS C

NOTES:

- CERAMIC TILE WALL IN TUB AND SHOWER AREAS SHALL HAVE CEMENT FIBER OR GLASS MAT BACKING BOARD AS PER TABLE R702.4.2
- WALL & CEILING FINISHES SHALL HAVE A FLAME SPREAD INDEX NOT GREATER THAN 200 PER R302.9.1 AND A SMOKE DEVELOPED INDEX NOT GREATER THAN 450 AS PER R302.9.2
- INSULATION MATERIAL SHALL HAVE A FLAME SPREAD INDEX OF NOT MORE THAN 25 & A SMOKE DEVELOPED INDEX OF NOT MORE THAN 450 PER R302.10.1
- WINDOW LOCATION SHALL BE VERIFIED WITH BUILDING ELEVATIONS TO ENSURE PROPER PLACEMENT. NOTIFY ARCHITECT OF ANY CONFLICTS.
- GLAZING IN BATH & SHOWER ENCLOSURE SHALL BE GLAZING CAT. II AS PER B2406.2
- GLAZING IN SLIDING & SWINGING DOORS SHALL BE SAFETY GLASS CAT. II IF LESS THAN 9 S.F. OR CAT. II IF GREATER THAN 9 S.F. AS PER TABLE B2406.2(1)
- GLAZING ADJACENT TO & WITHIN 48" OF A DOOR SHALL BE SAFETY GLAZING CAT.II AS PER B2406.4.2
- GLAZING WITHIN 60" OF FLOOR LEVEL IN WALLS SURROUNDING TUB OR SHOWER & WITHIN 60" HORIZONTALLY OF TUB OR SHOWER SHALL BE SAFETY GLAZING CAT. II AS PER B2406.4.5.1 & R308.4.5
- CONTRACTOR SHALL CHECK SHGC AND U-FACTOR FOR THE GLASS GLAZING. SUBMIT DOCUMENTATION FOR ARCHITECTS APPROVAL
- INTERIOR SITE APPLIED TO EMIT LOW VOC SHALL MEET SPECIFIED VOC EMISSIONS LIMITS IN ACCORDANCE WITH GREENGUARD ENVIRONMENTAL INSTITUTE GGPS.001 OF TOTAL VOCs ≤0.5 MG/M²
- WALL AND FINISH MATERIALS SHALL NOT EXCEED THE FLAME SPREAD CLASSIFICATION AS INDICATED ON GN-1 FINISH NOTE 1.
- ELEVATION CHANGE BETWEEN ADJACENT SPACES WITH DIFFERENT FLOOR FINISHES SHALL NOT EXCEED 1/2". PROVIDE TAPERING MATERIAL AS REQUIRED TO LEVEL TRANSITION.
- WALLS BATHROOMS AND KITCHEN PROVIDE FULL HEIGHT CERAMIC TILE AROUND ROOMS OVER CEMENT BOARD U.O.N.
- WATERPROOFED SLAB CONCRETE WITH SEALANT, EXCEPT FOR BALCONIES AND TERRACES THAT AREA ABOVE INTERIOR LIVING SPACES, WHICH WILL BE PROVIDED WITH A FULL INSULATED AND WATERPROOFED ROOF/ FLOORING FINISH PACKAGE
- ALL PORCELAIN, QUARRY, CERAMIC OR STONE TILE SHALL BE INSTALLED AS RECOMMENDED BY THE TILE COUNCIL OF AMERICA. SUBMIT INSTALLATION METHOD TO ARCHITECT FOR APPROVAL.
- GYPSUM BOARD FINISH:
 - ALL ROOMS RECEIVING SEMI-GLOSS OR SATIN PAINT SHALL RECEIVE A LEVEL 5 GYPSUM BOARD FINISH.
 - ALL ROOMS RECEIVING FLAT PAINT SHALL RECEIVE LEVEL4 GYPSUM BOARD FINISH.
 - GYPSUM BOARD FINISHES ACCORDING TO THE GYPSUM ASSOCIATION RECOMMENDATIONS.

ROOM FINISH SCHEDULE

ROOM NAME	FLOOR			WALLS												ROOF/CEILING			
				NORTH			EAST			SOUTH			WEST						
	MATL.	FIN.	BASE	MATL.	TEXTURE LEVEL	FIN.	MATL.	TEXTURE LEVEL	FIN.	MATL.	TEXTURE LEVEL	FIN.	MATL.	TEXTURE LEVEL	FIN.	MATL.	TEXTURE LEVEL	FIN.	HT. A.F.F.
LIVING/DINING ROOM UNDER BRIDGE	F1	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	SMOOTH MET	-	20'-6" 10'-0"
1st FLOOR ROOMS	F1	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	SMOOTH	-	10'-0"
2nd FLOOR ROOMS	F5	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	SMOOTH	-	9'-0"
BRIDGE	F5	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	8'-0"
STAIR	F5	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	SMOOTH	P-1	20'-6"
BATHROOMS	F1	-	-	WS WT1	-	-	WS WT1	-	-	WS WT1	-	-	WS WT1	-	-	GBMR	SMOOTH	P-1	VARIES
STAFF & UTILITY ROOM	F2	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	SMOOTH	P-1	10'-0"
STAFF BATH	F2	-	-	WT2	-	-	WT2	-	-	WT2	-	-	WT2	-	-	GBMR	SMOOTH	P-1	10'-0"
GARAGE	F4	-	-	GB	-	P-1	GB	-	P-1	GB	-	P-1	GB	-	P-1	ST	SMOOTH	P-1	12'-4"
COVERED TERRACE	F3	-	-	ST	-	P-1	ST	-	P-1	ST	-	P-1	ST	-	P-1	ST	SMOOTH	P-1	21'-0"

FINISH LEGEND (SUGGESTING CLADDING FINISH)

CAT.	CODE	DESCRIPTION	MANUFACTURER
PANT	P-1	PLASTER-WHITE	PAINTED BY CONTRACTOR
FLOORING	F1	OPUSTONE - ARDEN MARBLE 36" X 36" X 3/4"	BY CONTRACTOR
	F2	OPUSTONE - LIMESTONE: 16" X 24" TILE BIANCO LUNA	BY CONTRACTOR
	F3	OPUSTONE - MORE AVORIO 18" X 36"	BY CONTRACTOR
	F4	CONCRETE	BY CONTRACTOR
	F5	HARDWOOD SYSTEM. (T.B.D.)	BY CONTRACTOR
WALL	WS	OPUSTONE - MARBLE: 3/4" SLAB CREMA MARFIL ANTIQUE	BY CONTRACTOR
	WT1	OPUSTONE - MARBLE: 16" X 24" TILE CREMA MARFIL ANTQ.	BY CONTRACTOR
	WT2	OPUSTONE - LIMESTONE: 16" X 24" TILE BIANCO LUNA	BY CONTRACTOR
	ST	STUCCO	BY CONTRACTOR