



TGFU.R40623 - Roofing Systems

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Roofing Systems

Coastal Metal Roofing Sales LLC
10877 NW 33RD ST
DORAL, FL 33172 United States

R40623

BUILDING UNITS

Any UL Classified peel and stick underlayment may be used in conjunction with "VersaShield® Fire-Resistant Roof Deck Protection" and "VersaShield® Underlayment" in any of the following applicable systems.

Class A

1. Deck: C-15/32 Incline: Unlimited

Barrier Board: — 1/4-in., 1/2-in. or 5/8-in. thick Georgia Pacific Gypsum LLC "DensDeck® Roofboard", "DensDeck DuraGuard™ Roofboard" or "DensDeck Prime® Roofboard" or 5/8-in. thick "DensDeck® Fireguard® Roofboard" or "DensDeck Prime® Fireguard® Roofboard" or "DensDeck Prime® STORMX™ Roofboard" mechanically fastened with all butt joints in the barrier board staggered a minimum of 6-in. from the plywood roof deck butt joints.
Surfacing: — Coated steel or aluminum roofing panels designated "Coastal ML150" or "Coastal 5V", mechanically fastened.

2. Deck: C-15/32 Incline: Unlimited

Underlayment: — One ply GAF "VersaShield® Fire-Resistant Roof Deck Protection" or "VersaShield® Underlayment", mechanically fastened.
Ply Sheet: — One ply Type 30 base sheet or GAF "VersaShield® Fire-Resistant Roof Deck Protection" or "VersaShield® Underlayment" mechanically fastened.
Surfacing: — Coated steel roofing panels designated "Coastal ML150" or "Coastal 5V", mechanically fastened.

3. Deck: C-15/32 Incline: Unlimited

Underlayment: — Two plies GAF "VersaShield® Fire-Resistant Roof Deck Protection" or "VersaShield® Underlayment", mechanically fastened.
Surfacing: — Aluminum roofing panels designated "Coastal ML150" or "Coastal 5V", mechanically fastened.

4. Deck: C-15/32 or spaced sheathing Incline: Unlimited

Base Sheet (Optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or Polyglass USA Inc "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.
Underlayment: — One ply Polyglass USA Inc "Polystick XFR" self-adhered.
Insulation (Optional): — Any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.

Ply Sheet (Optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or

Polyglass USA Inc "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.
Surfacing: — Coated steel roofing panels designated "Coastal ML150" or "Coastal 5V", mechanically fastened.

5. **Deck:** C-15/32 or spaced sheathing **Incline:** Unlimited

Base Sheet (Optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or Polyglass USA Inc "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.
Underlayment: — Two plies Polyglass USA Inc "Polystick XFR" self-adhered.
Insulation (Optional): — Any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.
Ply Sheet (Optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or Polyglass USA Inc "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.
Surfacing: — Aluminum roofing panels designated "Coastal ML150" or "Coastal 5V" (minimum 0.032 inch), mechanically fastened.

Last Updated on 2021-07-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"