



"Delivering Excellence Every Day"

Miami-Dade County
HVHZ Electronic Roof Permit Form
Section D Metal Roof System

Roof System Manufacturer: METAL ROOFING SUPPLIERS LLC

Notice of Acceptance Number: 25-0127.07

Minimum Design Wind Pressures, (from RAS 127 or Calculations): P 1: -74 P 2: -98 P 3: -128

Maximum Design Wind Pressures, (From the NOA Specific system): -165 psf

Fill in the specific roof assembly components. If a component is not required, insert not applicable (n/a) in the text box.



Roof Slope: 4 "/12"

Roof Mean Height: 14 ft.

Clip or Screw Spacing for Metal Roof Panel Attachment

Field: 12 " o/c Perimeters: 12 " o/c Corners: 12 " o/c

Number of screws required per clip: 2

Perimeter Width: 3.5 ft.

Screw Type, Size, & Gauge for Clip or Metal Panel Attachment:

10 CARBON STEEL SCREW 1 1/8

Deck Type: --5/8" Plywood--

Optional Nailable Substrate:

N/A

Optional Nailable Substrate Attachment Method:

N/A

Optional Insulation:

N/A

Optional Insulation Attachment Method:

N/A

Fire Barrier:

POLYGLASS XFR (1 PLY) DIRECT DECK

Underlayment Type:

N/A

Underlayment Fastener Type:

1 1/4 RS NAIL HOT DIP GALVANIZED

Optional Peel & Stick Membrane:

N/A

Metal Roof Panel:

ENGLERT SERIES 1300 STEEL

Drip Edge Size & Gauge: --3" face 24 ga.--

Drip Edge Material Type: --Galvanized Metal--

Drip Edge Fastener Type: 4"1/4 RS NAIL

Hook Strip/Cleat gauge or weight: --24 ga.--