



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786)315-2590 F (786) 315-2599

www.miamidade.gov/economy

GAF

1 Campus Drive
Parsippany, NJ 07054

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: GAF EverGuard® TPO Single Ply Roofing Systems over Wood Decks.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA No. 20-0518.02 and consists of pages 1 through 32.

The submitted documentation was reviewed by Jorge L. Acebo.

08/28/25



NOA No.: 25-0707.01
Expiration Date: 09/22/30
Approval Date: 08/28/25
Page 1 of 32

ROOFING SYSTEM APPROVAL

Category: Roofing
Sub-Category: Single Ply Roofing
Material: TPO
Deck Type: Wood
Maximum Design Pressure: -120 psf.

TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:
TABLE 1

Product	Dimensions	Test Specification	Product Description
EverGuard® TPO	Various	ASTM D6878 TAS 131	Thermoplastic olefin reinforced single-ply membrane.
EverGuard Extreme® TPO	Various	ASTM D6878 TAS 131	Thermoplastic olefin reinforced single-ply membrane designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Fleece-back Membrane	Various	ASTM D 6878 TAS 131	Thermoplastic olefin reinforced, fleece back single-ply membrane
EverGuard Extreme® TPO Fleece-back Membrane	various	ASTM D6878 TAS 131	Thermoplastic olefin reinforced fleece back single-ply membrane designed for advanced protection against heat aging and UV degradation.
GAFGLAS® #75 Base Sheet	39.37" (1 meter) wide	ASTM D4601	Smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
Tri-Ply® #75 Base Sheet	39.37" (1 meter) wide	ASTM D4601	Smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
GAFGLAS® #80 Ultima™ Base Sheet	39.37" (1 meter) wide	ASTM D4601	Smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
Ruberoid® 20 Smooth	39.37" (1 meter) wide	ASTM D6163	SBS polymer-modified asphalt base or ply sheet reinforced with a fiberglass mat.
GAFGLAS® Stratavent® Nailable Venting Base Sheet	39.37" (1 meter) wide	ASTM D4897	Smooth surfaced asphaltic nailable venting base sheet reinforced with fiberglass mat. Bottom side surfaced with granules.
LRF Adhesive M	1:1 applicator	Proprietary	Two-part VOC free polyurethane foam adhesive.
LRF Adhesive O	1:1 applicator	Proprietary	Two-part VOC free polyurethane foam adhesive.

Product	Dimensions	Test Specification	Product Description
EverGuard® #1121 Bonding Adhesive	5 gallons	Proprietary	Solvent based adhesive for fully adhered TPO systems and membrane flashing.
EverGuard® WB 181 Bonding Adhesive	5 gallons	Proprietary	Water-based bonding adhesive for use with smooth TPO, fleece backed TPO and fleece backed PVC membranes.
EverGuard® Low VOC TPO Bonding Adhesive	5 gallons	Proprietary	Low VOC adhesive for TPO fully adhered systems and flashings.
VersaShield® Fire-Resistant Roof Deck Protection	12" x 100' rolls	ASTM D226	Non-asphaltic fiberglass reinforced underlayment and /or fire barrier.
VersaShield® Solo™ Fire-Resistant Slip Sheet	42" roll wide, 100 ft.	ASTM D146, D828, D4869, D6757	Non-asphaltic, fire-resistant fiberglass underlayment.
EverGuard® TPO Coated Metal	4' x 10' sheets	Proprietary	24-gauge steel with a 25-mil thick GAF TPO for edge detailing.
EverGuard Extreme® TPO Coated Metal	4' x 10' sheets	Proprietary	24-gauge steel with a 25-mil thick GAF TPO for edge detailing and designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Cover Tape	6" x 100' 10" x 100'	Proprietary	GAF TPO laminated to white butyl tape primarily used for edge metal details.
EverGuard® TPO Cover Tape Heat-Weld	6" x 100'	Proprietary	Flashing strip manufactured from unreinforced GAF TPO laminated to a six-inch-wide strip, half the strip with a self-adhered side and half the strip with a heat-weldable edge; used for edge metal details.
EverGuard Extreme® TPO Cover Tape Heat-Weld	6" x 100'	Proprietary	Flashing strip manufactured from unreinforced GAF TPO designed for advanced protection against heat aging and UV degradation. Laminated to a six-inch-wide strip, half the strip with a self-adhered side and half the strip with a heat-weldable edge; used for edge metal details.
EverGuard® TPO Detailing Membrane	24" x 50'	Proprietary	Unreinforced flashing material manufactured from GAF TPO.

Product	Dimensions	Test Specification	Product Description
EverGuard Extreme® TPO Detailing Membrane	24" x 50'	Proprietary	Unreinforced flashing material manufactured from GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Flashing Strip	Various	Proprietary	Reinforced flashing membrane manufactured from GAF TPO.
EverGuard Extreme® TPO Flashing Strip	Various	Proprietary	Reinforced flashing membrane manufactured from GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Pourable Sealer Pocket	9" x 6" x 4" oval with 3" base flange	Proprietary	Pourable sealer pocket is molded with GAF TPO compound to a nominal 70 mil thickness designed for waterproofing irregular shaped roof penetrations.
EverGuard Extreme® TPO Pourable Sealer Pocket	9" x 6" x 4" oval with 3" base flange	Proprietary	Pourable sealer pocket is molded from GAF TPO designed for advanced protection against heat aging and UV degradation compounded to a nominal 70 mil thickness designed for waterproofing irregular shaped roof penetrations.
EverGuard® TPO RTA Strip™	6" x 100' roll	Proprietary	Reinforced GAF TPO membrane with pressure sensitive adhesive primarily used to secure membrane transitions from the field to vertical surfaces.
EverGuard Extreme® TPO RTA Strip™	6" x 100' roll	Proprietary	Reinforced GAF TPO membrane with pressure sensitive adhesive primarily used to secure membrane transitions from the field to vertical surfaces.
EverGuard® TPO Split Pipe Boot	1" - 2" 3" - 5" 6" - 8"	Proprietary	Reinforced GAF TPO membrane split to accommodate most common pipes and conduits.
EverGuard Extreme® TPO Split Pipe Boot	1" - 2" 3" - 5" 6" - 8"	Proprietary	Reinforced GAF TPO designed for advanced protection against heat aging and UV degradation split to accommodate most common pipes and conduits.
EverGuard® TPO Square Tube Wrap	4" x 4" 4" x 6" 6" x 6"	Proprietary	Reinforced GAF TPO with split design overlap to be wrapped around square or rectangular tubing.

Product	Dimensions	Test Specification	Product Description
EverGuard Extreme® TPO Square Tube Wrap	4" x 4" 4" x 6" 6" x 6"	Proprietary	Reinforced GAF TPO designed for advanced protection against heat aging and UV degradation with split design overlap to be wrapped around square or rectangular tubing.
EverGuard® TPO Corner Curb Wrap	Various	Proprietary	Corners fabricated from reinforced GAF TPO.
EverGuard Extreme® TPO Corner Curb Wrap	Various	Proprietary	Corners fabricated from reinforced GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Scupper	4" x 6" x 12" 8" x 10" x 12"	Proprietary	Scupper manufactured from coated metal and unreinforced GAF TPO.
EverGuard® TPO T-Joint Cover Patch	100 patches per box	Proprietary	T-Joint patch manufactured from unreinforced GAF TPO.
EverGuard Extreme® TPO T-Joint Cover Patch	100 patches per box	Proprietary	T- Joint patch manufactured from unreinforced GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Vent	2 vents per carton	Proprietary	Vent manufactured from reinforced GAF TPO membrane and galvanized steel.
EverGuard® TPO T-Top Vent	4" or 6"	Proprietary	Vent manufactured from reinforced GAF TPO membrane and galvanized steel.
EverGuard® TPO Walkway Rolls	Rolls 1/8" x 30" x 50'	Proprietary	Standard duty TPO walkway rolls.
EverGuard® TPO Inside Corner	6" x 6" x 5 1/4"	Proprietary	Inside corner manufactured from unreinforced GAF TPO.
EverGuard Extreme® TPO Inside Corner	6" x 6" x 5 1/4"	Proprietary	Inside corner manufactured from unreinforced GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® TPO Universal Corners	various	Proprietary	Universal corners manufactured from GAF TPO that are heat seamable and designed to accommodate both inside and outside corners of base and curb flashings manufactured from GAF TPO.

Product	Dimensions	Test Specification	Product Description
EverGuard Extreme® TPO Universal Corners	various	Proprietary	Universal corners manufactured from GAF TPO designed for advanced protection against heat aging and UV degradation are heat seamable and designed to accommodate both inside and outside corners of base and curb flashings.
EverGuard® TPO Vent Boot	1" - 6" o.d. 6 pcs. crtn.	Proprietary	Vent pipe boot molded from GAF TPO and supplied with stainless steel clamping rings.
EverGuard Extreme® TPO Vent Boot	1" - 6" o.d. 6 pcs. crtn.	Proprietary	Vent pipe boot molded from GAF TPO designed for advanced protection against heat aging and UV degradation and supplied with stainless steel clamping rings.
EverGuard® TPO Expansion Joint Cover	various	Proprietary	Low profile joint cover manufactured from reinforced GAF TPO.
EverGuard® Extreme TPO Expansion Joint Cover	various	Proprietary	Low profile joint cover manufactured from reinforced GAF TPO.
EverGuard® TPO Cut Edge Sealant	1 quart squeeze tube	Proprietary	Clear solvent-based sealant for TPO cut edges.
EverGuard® Low VOC Cut Edge Sealant	1 quart squeeze tube	Proprietary	Low VOC clear solvent-based sealant for TPO cut edges.
EverGuard® TPO Drain	various	Proprietary	Spun aluminum drain pre-flashed with unreinforced GAF TPO.
EverGuard® TPO Seam Cleaner	1 gallon	Proprietary	Solvent based seam cleaner.
EverGuard® TPO Primer	1 gallon	Proprietary	Solvent-based VOC compliant TPO primer
EverGuard® TPO Low VOC Primer	1 gallon	Proprietary	Low VOC TPO primer
EverGuard® TPO Standing Seam Tape	6"	Proprietary	White butyl cover tape.
EverGuard® TPO Standing Seam Profile	10' length 1 ½" base 1 ¼" vertical rib	Proprietary	Accessory applied over GAF TPO roofing systems to simulate a standing seam metal roof.
EverGuard® TPO Fluted Corner	8" diameter nominal .05" non-reinforced	Proprietary	Flashing for outside corners of base and curb flashing manufactured from non-reinforced GAF TPO.

Product	Dimensions	Test Specification	Product Description
EverGuard Extreme® TPO Fluted Corner	8" diameter nominal .05" non-reinforced	Proprietary	Flashing for outside corners of base and curb flashing manufactured from non-reinforced GAF TPO designed for advanced protection against heat aging and UV degradation.
EverGuard® CleanWeld™ Conditioner	1 gallon	Proprietary	Low VOC cleaner for TPO
TPO Red Primer	1 gallon	Proprietary	Solvent-based primer for TPO membranes
FireOut™ Fire Barrier Coating	5 or 55 gallons	Proprietary	Low VOC, water-based fire barrier coating.
EverGuard® 3 Square Low VOC TPO Bonding Adhesive	5 Gallons	Proprietary	Low VOC TPO bonding adhesive that provides 3 square coverage per pail.
EverGuard® TPO Quick Spray Adhesive	40.15 lbs.	Proprietary	Sprayable solvent based adhesive for fully adhered TPO systems and membrane flashing.
EverGuard® TPO Quick Spray Adhesive LV50	36.3 lbs.	Proprietary	Sprayable Low VOC solvent-based adhesive for fully adhered TPO systems and membrane flashing.

APPROVED INSULATIONS:

TABLE 2

Product Name	Product Description	Manufacturer (With Current NOA)
EnergyGuard™ Polyiso Insulation	Polyisocyanurate foam insulation	GAF
EnergyGuard™ HD Polyiso Insulation	High density polyisocyanurate foam insulation	GAF
EnergyGuard™ HD Plus Polyiso Insulation	High density polyisocyanurate foam insulation	GAF
EnergyGuard™ Ultra Polyiso Insulation	Glass-faced polyisocyanurate foam insulation.	GAF
EnergyGuard™ RA Polyiso Insulation	Polyisocyanurate foam insulation	GAF
DensDeck® Roof Board	Gypsum board	Georgia Pacific Gypsum LLC
SECUROCK® Gypsum-Fiber Roof Board	Gypsum board	United States Gypsum Corporation
SECUROCK® Glass-Mat Roof Board	Glass faced gypsum board	United States Gypsum Corporation
Structodek® High Density Fiberboard Roof Insulation	High-density fiberboard	Blue Ridge FiberBoard, Inc.

APPROVED FASTENERS:

TABLE 3
Product
Description

Fastener Number	Product Name	Product Description	Dimensions	Manufacturer (With Current NOA)
1.	Drill-Tec™ #12 Fastener	Phillips head, modified buttress thread, pinch point, carbon steel fastener for use in steel or wood decks. With CR-10 coating. Available with a pinch point or drill point.	#12 x 8" max. length, #3 Phillips head	GAF
2.	Drill-Tec™ #14 Fastener	Truss head, self-drilling, pinch point, high thread fastener for use in steel, wood or concrete decks.	#14 x 16" max. Length, #3 Phillips head.	GAF
3.	Drill-Tec™ AccuTrac® Recessed Plate	Galvalume® steel plate with recess for use with Drill-Tec™ fasteners.	3" square; .017" thick.	GAF
4.	Drill-Tec™ AccuTrac® Flat Plate	A2-SS aluminized steel plate for use with Drill-Tec™ fasteners.	3" square; .017" thick	GAF
5.	Drill-Tec™ 2-3/8 in. Barbed XHD Plate	Round galvanized steel stress plates for use with Drill-Tec™ fasteners.	2-3/8" round	GAF
6.	Drill-Tec™ 2 in. Double Barbed XHD Plate	Round galvanized steel stress plates for use with Drill-Tec™ fasteners.	2" round	GAF
7.	Drill-Tec™ Eyehook AccuSeam Plate	Round Galvalume® steel plate for use with Drill-Tec™ fasteners.	2-3/8" round	GAF
8.	Drill-Tec™ 3" Steel Plate	Round Galvalume® steel stress plate with reinforcing ribs and recessed for use with Drill-Tec™ fasteners.	3" round	GAF
9.	Drill-Tec™ 3" Standard Steel Plate	Galvalume® coated steel stress plate for use with approved Drill-Tec™ fasteners.	3" round	GAF
10.	Drill-Tec™ 3 in. Ribbed Galvalume Plate (Flat)	Round Galvalume® plated steel stress plate with reinforcing ribs for use with Drill-Tec™ fasteners.	3" round	GAF
11.	Drill-Tec™ ASAP 3S	Drill-Tec™ #12 Fastener with Drill-Tec™ 3" Standard Steel Plate.	See Components	GAF
12.	Drill-Tec™ RhinoBond® TPO XHD Plate	Gold primer coated plate for use with TPO membranes.	3" Round	GAF
13.	Drill-Tec™ RhinoBond® TPO XHD TreadSafe Plate	Round, coated Galvalume® plate (Gold primer coating) used for TPO membranes.	3" Round	GAF

EVIDENCE SUBMITTED:

<u>Test Agency/Identifier</u>	<u>Name</u>	<u>Report</u>	<u>Date</u>
UL LLC	03CA38009	UL 790	01/21/04
	08CA37926	UL 790	09/23/09
	08CA49140	UL 790	09/23/09
	R1306	UL 790	07/04/25
	R10689	UL 790	07/25/25
FM Approvals	3B9Q1.AM	FM 4470	01/08/98
	3020588	FM 4470	03/24/04
	3023458	FM 4470	07/18/06
	3026964	FM 4470	07/25/07
	3029832	FM 4470	05/11/07
	3033135	FM 4470	11/24/08
	3035658	FM 4470	09/16/09
	3038278	FM 4470	11/18/11
	3038318	FM 4470	12/10/10
	3036980	FM 4470	08/14/09
	3040377 LTR	FM 4470	09/21/16
	3040738	FM 4470	11/16/10
	3041769	FM 4470	05/26/11
	3042905	FM 4470	01/10/12
	3045166	FM 4470	07/24/12
	3045363	FM 4470	10/12/12
	3047636	FM 4470	08/08/13
	3053501	FM 4470	01/14/16
	PR449764	FM 4470	07/25/18
	RR210305	FM 4470	06/18/17
	RR221253	FM 4470	02/07/20
IRT-ARCON	02-005	TAS 114	01/24/02
	02-008	TAS 114	01/24/02
Atlantic & Caribbean Roof Consulting, LLC	08-022-R1	TAS 114	01/15/15
	11-056-R2	TAS 114	01/26/15
Exterior Research & Design, L.L.C.	01509.03.04-2	TAS 114-J	03/16/04
Trinity-ERD	SC10680.05.16	ASTM D6163	05/10/16
NEMO ETC, LLC	4q-GAF-19-SSMBB-02.A	ASTM D6163	04/08/19
PRI Construction Materials Technologies, LLC	GAF-122-02-01	TAS 139	05/07/06
	GAF-306-02-01	ASTM E96	08/23/11
	GAF-349-02-01	TAS 110	07/03/12
	GAF-434-02-01	TAS 117	09/16/13
	GAF-435-02-01	TAS 117(B)	01/29/14
	GAF-462-02-01	ASTM D413	11/18/13
	GAF-462-02-02	TAS 117(B)	11/18/13
	GAF-462-02-09	TAS 114	07/01/14

EVIDENCE SUBMITTED: (CONTINUED)

<u>Test Agency/Identifier</u>	<u>Name</u>	<u>Report</u>	<u>Date</u>
PRI Construction Materials Technologies, LLC	GAF-462-02-10	TAS 114	07/01/14
	GAF-462-02-11	TAS 114	07/01/14
	GAF-508-02-01	Various	03/12/14
	GAF-515-02-01	TAS 114	05/13/14
	GAF-516-02-01	TAS 114	05/13/14
	GAF-516-02-02	TAS 114	06/06/14
	GAF-516-02-03	TAS 114	05/13/14
	GAF-559-02-01	TAS 117	10/16/14
	GAF-559-02-04	ASTM D1876	03/04/15
	GAF-559-02-11	TAS 114	10/16/14
	GAF-559-02-12	TAS 114	10/16/14
	GAF-559-02-13	TAS 114	10/16/14
	GAF-559-02-15	TAS 114	10/16/14
	GAF-559-02-16	TAS 114	10/16/14
	GAF-559-02-18	TAS 114	10/16/14
	GAF-567-02-01	ASTM D1876	01/23/15
	GAF-746-02-05	TAS 114	12/14/16
	GAF-746-02-06	TAS 114	12/14/16
	GAF-836-02-01	TAS 114	03/02/18
	GAF-836-02-02	TAS 114	03/02/18
	GAF-836-02-03	TAS 114	03/02/18
	GAF-836-02-04	TAS 114	03/02/18
	PRI 376T0017	TAS 114	08/09/19
	PRI 376T0025	TAS 114	09/06/19
	PRI 376T0026	TAS 114	09/06/19
	PRI 376T0027	TAS 114	09/19/19
	PRI 376T0227	ASTM D4897	12/20/21
	PRI 376T0229	ASTM D4601	12/20/21
	PRI 376T0240	ASTM D4601	12/21/21
	PRI 376T0270	Proprietary	01/14/22
	PRI 376T0466	Proprietary	10/24/23

Membrane Type: Single Ply, TPO

Deck Type 1I: Wood, Insulated

Deck Description: Min. 19/32" thick plywood attached to structural wood supports spaced maximum 24" o.c. using 8d ring shank nails spaced 4" o.c. at panel end and intermediate supports.

System Type D(3): All insulation is loose laid with preliminary attachment to roof deck. Membrane is subsequently mechanically fastened through insulation to wood deck.

All General and System Limitations apply. Roof accessories not listed in Table 1 of this NOA are not approved and shall not be installed unless said accessories demonstrate compliance with prescriptive Florida Building Code requirements and are field fabricated utilizing the approved membranes listed in Table 1.

Fire Barrier: DensDeck® Roof Board, SECUROCK® Gypsum-Fiber Roof Board, SECUROCK® Glass-Mat Roof Board, minimum 1/4" thick (see insulation note below for preliminary attachment details).
(Optional) OR
 VersaShield® Fire-Resistant Roof Deck Protection, VersaShield® Solo™ Fire-Resistant Slip Sheet or FireOut™ Fire Barrier Coating applied per manufacturer's installation instructions.

One or more layers of any of the following.

Base Insulation Layer	Insulation Fasteners (Table 3)	Fastener Density/ft ²
EnergyGuard™ Polyiso Insulation, EnergyGuard™ RA Polyiso Insulation, EnergyGuard™ RN Polyiso Insulation, EnergyGuard™ Ultra Polyiso Insulation, EnergyGuard™ HD Polyiso Insulation, EnergyGuard™ HD Plus Polyiso Insulation Minimum 0.5" thick	N/A	N/A
Top Insulation Layer (Optional)	Insulation Fasteners (Table 3)	Fastener Density/ft ²
Dens Deck® Roof Board, SECUROCK® Gypsum-Fiber Roof Board, SECUROCK® Glass-Mat Roof Board Minimum 0.25" thick	N/A	N/A

Insulation Note: All insulation shall have preliminary attachment prior to the installation of the roofing membrane at a minimum application rate of two fasteners per board for insulation boards having no dimension greater than 4 ft. and four fasteners for any insulation board having no dimension greater than 8 ft. Please refer to Roofing Application Standard RAS 117 for insulation attachment requirements.

Membrane: EverGuard® TPO or EverGuard Extreme® TPO mechanically fastened using Drill-Tec™ #14 Fasteners and Drill-Tec™ 2 in. Double Barbed XHD Plates, Drill-Tec™ 2-3/8 in. Barbed XHD Plates or Drill-Tec™ Eyehook AccuSeam Plates spaced maximum 8" o.c. in fastener rows spaced maximum 55" o.c. The minimum 5" wide side laps are sealed with minimum 1.5" wide heat welds for automatic machine welding or with minimum 2" welds for hand welding.

Maximum Design Pressure: -45 psf. (See General Limitation #7)



GENERAL LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Insulation may be installed in multiple layers. The first layer shall be attached in compliance with Product Control Approval guidelines. All other layers shall be adhered in a full mopping of approved asphalt applied within the EVT range and at a rate of 20-40 lbs./sq., or mechanically attached using the fastening pattern of the top layer
3. All standard panel sizes are acceptable for mechanical attachment. When applied in approved asphalt, panel size shall be 4' x 4' maximum.
4. An overlay and/or recovery board insulation panel is required on all applications over closed cell foam insulations when the base sheet is fully mopped. If no recovery board is used the base sheet shall be applied using spot mopping with approved asphalt, 12" diameter circles, 24" o.c.; or strip mopped 8" ribbons in three rows, one at each side lap and one down the center of the sheet allowing a continuous area of ventilation. Encircling of the strips is not acceptable. A 6" break shall be placed every 12' in each ribbon to allow cross ventilation. Asphalt application of either system shall be at a minimum rate of 12 lbs./sq.

Note: Spot attached systems shall be limited to a maximum design pressure of -45 psf.

5. Fastener spacing for insulation attachment is based on a Minimum Characteristic Force (F') value of 275 lbf. as tested in compliance with Testing Application Standard TAS 105. If the fastener value, as field-tested, are below 275 lbf. insulation attachment shall not be acceptable.
6. Fastener spacing for mechanical attachment of anchor/base sheet or membrane attachment is based on a minimum fastener resistance value in conjunction with the maximum design value listed within a specific system. Should the fastener resistance be less than that required, as determined by the Building Official, a revised fastener spacing, prepared, signed and sealed by a Florida Registered Engineer, Architect, or Registered Roof Consultant may be submitted. Said revised fastener spacing shall utilize the withdrawal resistance value taken from Testing Application Standards TAS 105 and calculations in compliance with Roofing Application Standard RAS 117.
7. Perimeter and corner areas shall comply with the enhanced uplift pressure requirements of these areas. Fastener densities shall be increased for both insulation and base sheet as calculated in compliance with Roofing Application Standard RAS 117 and/or RAS 137. Calculations prepared, signed and sealed by a Florida registered Professional Engineer, Registered Architect, or Registered Roof Consultant **(When this limitation is specifically referred within this NOA, General Limitation #9 will not be applicable.)**
8. All attachment and sizing of perimeter nailers, metal profile, and/or flashing termination designs shall conform to Roofing Application Standard RAS 111 and applicable wind load requirements.
9. The maximum designed pressure limitation listed shall be applicable to all roof pressure zones (i.e. field, perimeters, and corners). Neither rational analysis, nor extrapolation shall be permitted for enhanced fastening at enhanced pressure zones (i.e. perimeters, extended corners and corners). **(When this limitation is specifically referred within this NOA, General Limitation #7 will not be applicable.)**
10. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE



Insulation (Optional): — "EnergyGuard™" or "EnergyGuard™ NH" or "EnergyGuard™ Ultra" or "EnergyGuard™ NH Ultra" or "EnergyGuard™ RN" or Hunter Panels "H-shield", or wood fiber or glass fiber or perlite, any thickness, mechanically fastened.

Insulation: — Minimum 1-1/2 in. thick "EnergyGuard™ Ultra" or "EnergyGuard™ NH Ultra" or minimum 1/2-in. thick "EnergyGuard™ Barrier" or "EnergyGuard™ HD Barrier" or "EnergyGuard™ NH Barrier" mechanically fastened with butt joints in the insulation staggered a minimum of 12-in. from butt joints in plywood roof deck.

Membrane: — "EverGuard® TPO FB Ultra" or "EverGuard® TPO Fleece-Back Membrane" 45-mil to 80-mil or "EverGuard Extreme® TPO FB Ultra" or "EverGuard Extreme® TPO Fleece-Back Membrane" 50-mil to 80-mil, fully adhered with "EverGuard® H2O Bonding Adhesive" or "EverGuard® WB 181 Bonding Adhesive", applied at a rate of 120-ft.²/gal. or adhered with "LRF Adhesive M" or "LRF Adhesive O", applied as a nominal 3/4-in. diameter bead with a maximum on-center spacing of 12-in., applied parallel to the incline of the roof.

Class C – Fully Adhered

1. Deck: NC

Incline: 1/2

Insulation: — "EnergyGuard™" or "EnergyGuard™ NH" or "EnergyGuard™ Ultra" or "EnergyGuard™ NH Ultra" or "EnergyGuard™ RA" or "EnergyGuard™ RA Tapered" or "EnergyGuard™ RA Ultra" or "EnergyGuard™ RA Ultra Tapered" or "EnergyGuard™ RA HD" or "EnergyGuard™ RN" or "EnergyGuard™ RF" or "EnergyGuard™ RM" or wood fiber or glass fiber or perlite, any thickness.

Cover Board (Optional): — 1/2-in. thick "EnergyGuard™ HD", "EnergyGuard™ HD Plus", "EnergyGuard™ HD Barrier" or "EnergyGuard™ NH HD" or "EnergyGuard™ NH HD Plus" or minimum 1.5-in. thick "EnergyGuard™ Polyiso – HD Composite Insulation" or "Ultra HD Composite Insulation", mechanically fastened

Membrane: — "EverGuard® TPO" 45-mil to 60-mil or "EverGuard Extreme® TPO" 50-mil to 60-mil, fully adhered with "EverGuard® #1121 Bonding Adhesive" or "EverGuard TPO 1121 Bonding Adhesive" or "EverGuard® TPO 3 Square Low VOC Bonding Adhesive" applied at a rate of 60-ft.²/gal.

2. Deck: C-15/32

Incline: Unlimited

Base Sheet: — One ply "VersaShield® Fire-Resistant Roof Deck Protection", mechanically fastened.

Insulation: — "EnergyGuard™" or "EnergyGuard™ NH" or "EnergyGuard™ RF" or "EnergyGuard™ Ultra" or "EnergyGuard™ NH Ultra" or "EnergyGuard™ RA" or "EnergyGuard™ RA Tapered" or "EnergyGuard™ RA Ultra" or "EnergyGuard™ RA Ultra Tapered" or "EnergyGuard™ RA HD" or "EnergyGuard™ RN" or "EnergyGuard™ RM", any thickness, any combination.

Cover Board (Optional): — 1/2-in. thick "EnergyGuard™ HD" or "EnergyGuard™ HD Plus", "EnergyGuard™ HD Barrier" or "EnergyGuard™ NH HD" or "EnergyGuard™ NH HD Plus" or minimum 1.5-in. thick "EnergyGuard™ Polyiso – HD Composite Insulation" or "Ultra HD Composite Insulation", mechanically fastened.

Membrane: — 45 to 80-mil thick "EverGuard® TPO FB Ultra" or "EverGuard® TPO Fleece-Back Membrane" or 50 to 80-mil thick "EverGuard Extreme® TPO FB Ultra" or "EverGuard Extreme® TPO Fleece-Back Membrane", adhered with "EverGuard® WB 181 Bonding Adhesive", applied at a rate of 0.83-gal./100-ft.²; or 45 to 80-mil thick "EverGuard® Freedom™ TPO HW", self-adhered.

3. Deck: NC

Incline: 1/4

Insulation (Optional): — "EnergyGuard™" or "EnergyGuard™ NH" or "EnergyGuard™ Ultra" or "EnergyGuard™ NH Ultra" or "EnergyGuard™ RA" or "EnergyGuard™ RA Tapered" or "EnergyGuard™ RA Ultra" or "EnergyGuard™ RA Ultra Tapered" or "EnergyGuard™ RA HD" or "EnergyGuard™ RN" or "EnergyGuard™ RF" or "EnergyGuard™ RM" or wood fiber or glass fiber or perlite, any thickness.

Membrane: — “EverGuard® TPO FB Ultra” or “EverGuard® TPO Fleece-Back Membrane” or “EverGuard® TPO Fleece-Back Membrane 100”, “EverGuard® TPO Fleece-Back Membrane 115”, or “EverGuard® TPO Fleece-Back Membrane 135” 45 to 80 mil, or “EverGuard Extreme® TPO FB Ultra” or “EverGuard Extreme® TPO Fleece-Back Membrane” 50-mil to 80-mil, mechanically fastened.

19. **Deck:** C-15/32

Incline: 2-1/2

Slip Sheet: — One or more plies “VersaShield® Solo™ Fire Resistant Slipsheet” mechanically fastened.

Membrane: — 45 to 60-mil “EverGuard® TPO” or “EverGuard® Extreme® TPO” mechanically attached.

20. **Deck:** C-15/32

Incline: 3/4

Slip Sheet: — One or more plies “VersaShield® Solo™ Fire Resistant Slipsheet” mechanically fastened.

Membrane: — 80-mil “EverGuard® TPO” or “EverGuard® Extreme® TPO”, mechanically attached.

21. **Deleted**

22. **Deck:** C-15/32

Incline: 1/2

Insulation (Optional): — “EnergyGuard™” or “EnergyGuard™ NH” or “EnergyGuard™ Ultra” or “EnergyGuard™ NH Ultra” or “EnergyGuard™ RN” or Hunter Panels “H-shield”, or wood fiber or glass fiber or perlite, any thickness, mechanically fastened.

Insulation: — “Minimum 3-in. thick “EnergyGuard™ Ultra” or “EnergyGuard™ NH Ultra” mechanically fastened with butt joints in the insulation staggered a minimum of 12-in. from butt joints in plywood roof deck.

Membrane: — “EverGuard® TPO” 45-mil to 80-mil or “EverGuard® Extreme™ TPO” 50-mil to 80-mil mechanically fastened.

23. **Deck:** C-15/32

Incline: 1/2

Insulation (Optional): — “EnergyGuard™” or “EnergyGuard™ NH” or “EnergyGuard™ Ultra” or “EnergyGuard™ NH Ultra” or “EnergyGuard™ RN” or Hunter Panels “H-shield”, or wood fiber or glass fiber or perlite, any thickness, mechanically fastened.

Insulation: — Minimum 1/2-in. thick “EnergyGuard™ Barrier” or “EnergyGuard™ HD Barrier” or “EnergyGuard™ NH Barrier” mechanically fastened with butt joints in the insulation staggered a minimum of 12-in. from butt joints in plywood roof deck.

Membrane: — “EverGuard® TPO” 45-mil to 80-mil or “EverGuard® Extreme™ TPO” 50-mil to 80-mil mechanically fastened.

24. **Deck:** C-15/32

Incline: 1/2

Base Sheet (Optional): — One ply “Liberty™ SBS Self-Adhering Base/Ply Sheet” or “RUBEROID® SA Base/Ply Sheet” or “Ruberoid® SA Universal Base Sheet” self-adhered.

Slip Sheet: — One or more plies “VersaShield® Solo™ Fire Resistant Slip Sheet”, mechanically fastened.

Insulation: — “EnergyGuard™” or “EnergyGuard™ NH” or “EnergyGuard™ Ultra” or “EnergyGuard™ NH Ultra” or “EnergyGuard™ RF” or “EnergyGuard™ RA” or “EnergyGuard™ RA Tapered” or “EnergyGuard™ RA Ultra” or “EnergyGuard™ RA Ultra Tapered” or “EnergyGuard™ RA HD” or “EnergyGuard™ RN” or “EnergyGuard™ RM” or “EnergyGuard™ Barrier” or “EnergyGuard™ HD Barrier” or “EnergyGuard™ NH Barrier”, any thickness, mechanically fastened.
