



"Delivering Excellence Every Day"

Miami-Dade County
HVHZ Electronic Roof Permit Form
Section D Metal Roof System

Roof System Manufacturer: METAL ROOFING SUPPLIERS

Notice of Acceptance Number: 25-0127.07

Minimum Design Wind Pressures, (from RAS 127 or Calculations): P 1: -74 P 2: -108 P 3: -128

Maximum Design Wind Pressures, (From the NOA Specific system): - 165 psf

Fill in the specific roof assembly components. If a component is not required, insert not applicable (n/a) in the text box.



Roof Slope: 3 "/12"

Roof Mean Height: 12 ft.

Clip or Screw Spacing for Metal Roof Panel Attachment

Field: 24 " o/c Perimeters: 12 " o/c Corners: 12 " o/c
2" CLIPS 6" CLIPS 6" CLIPS

Number of screws required per clip: 3

Perimeter Width: 3 ft.

Screw Type, Size, & Gauge for Clip or Metal Panel Attachment:

#10 PANCAKE 1.25

Deck Type: --5/8" Plywood--

Optional Nailable Substrate:

N/A

Optional Nailable Substrate Attachment Method:

N/A

Optional Insulation:

N/A

Optional Insulation Attachment Method:

N/A

Fire Barrier:

POLLYGLASS XFR

Underlayment Type:

POLLYGLASS MTX

Underlayment Fastener Type:

SELF ADHERED

Optional Peel & Stick Membrane:

POLLYGLASS MTX

Metal Roof Panel:

16" ENGLERT SERIES 1300 STEET

Drip Edge Size & Gauge: --3" face 26 ga.--

Drip Edge Material Type: --Galvanized Metal--

Drip Edge Fastener Type: 1.25 RS 4" O.C

Hook Strip/Cleat gauge or weight: -- Select Hook Strip --