

Roofing Systems

See General Information for Roofing Systems

TREMCO INC

R10845

4475 E 175TH ST

CLEVELAND, OH 44128-3411 USA

1/2 in. thick (min) gypsum board or G-P Gypsum DensDeck® may be used in any existing noncombustible deck Classification. When this is done, the resulting roofing system is acceptable for use over combustible (15/32 in. min) roof decks. The joints in the gypsum board and overlayment board are offset 6 in. with the joints in the deck.

FLUID APPLIED COATING SYSTEMS

Class A

5. Deck: NC

Incline: 1-1/2

Primer (Optional): — "No. 171", 250 sq ft/gal.

Base Coat: — "Vulkem 350NF-R" or "Vulkem 350NF-S/L", 55 sq ft/gal.

Top Coat: — "Vulkem 351NF" or "346NF", 125 sq ft/gal.

Surfacing: — Silica sand, 4-8 lbs/100 sq ft

System Identification: — "Pedestrian Deck".

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"